

The limited liability company "SWAN-NN"

TIN/TRRC 5249099445/524901001

606000, Nizhny Novgorod Region, Dzerzhinsk, Nauki St., 12 "B" Ph./fax: (8313) 31-01-74, 31-45-81

e-mail: info@swan-nn.ru, www.swan-nn.ru

Solta-200 seriesOverprint varnish

Technical specification TV 2313-011-57845504-2005

Overprint varnish is a composition of an acrylic binder and indirect materials. Solta-200 series is used for paper and wallcoverings waterproofing in moisture-resistant materials production.

Physico-chemical properties

item	values for each grade	
	Solta-202 Solta-202-01	Solta-202B Solta-202B-01
1. Appearance	milk-white liquid free of foreign matter	
2. Non-volatile matter content, %, minimum	25	40
3. pH	7 - 9	7 - 8
4. Funnel viscosity VS-246 flowmeter type, 6 mm jet size, minimum	30	11

Application guideline

Solta-202, Solta-202-01 (newly-designed product) are required to be watered down up to the press viscosity.

Solta-202B, Solta-202B-01 (newly-designed product) – practically finished composition with 13-16 s.viscosity.

Storage instructions

Varnishes Solta 200 series stability is guaranteed within 6 months period in close containers at temperatures of 5-30 °C.